

# LANDEX

# 3.0RT

Suppliers of  
**XCMG**  
Construction Machinery

## Landex Rough Terrain 3 tonne Forklift



- CPCD30RT forklift
- Isuzu (Japan) 60hp Diesel
- Automatic Difflock
- Triplex Container Mast
- Hydraulic Side Shift
- Hydraulic Transmission (TCM technology)
- 4.0m max height
- 1m diameter front tyre
- Simple to operate
- Flashing beacon
- Reverse alarm
- Fork positioning available



Sales  
022 6188 456

ph 0800 LANDEX (0800 526 339)

Address: 9-13 Sims Rd, Penrose



e-mail: [sales@landex.co.nz](mailto:sales@landex.co.nz)

Postal: PO Box 58413, Botany, Manukau 2163

Parts and Service  
0220 693 571

Website: [www.landex.co.nz](http://www.landex.co.nz)



## Model K3.0 RT

Power type	Isuzu Diesel
Rated capacity	3000 kg
Load center	500 mm
Maximum lift height	4000 mm
Free lift height	150 mm
Operating Weight	5050 kg
Fork size L*W*T	1070*125*45 mm
Mast inclination Front/Back	10/12 degrees
Front overhang mm	479 mm

### Overall dimensions

Length to face of fork	3074 mm
Length with Forks	4144 mm
Overall width	1550 mm
Mast lowered height	2325mm
Overhead guard height	2290 mm
Turning radius	3635 mm

### Performance

Travel speed no load	20 km/h
Lift speed mm/s	450/500 mm/s
Max. gradeability %	18 %
Max. drawbar pull Kn	16.5 kN
Tyres Front	15-19.5--14PR
Rear	10-16.5 8PR
Wheel Centres Front	1160 mm
Rear	1100 mm
Wheelbase	1900 mm
Min. ground clearance	F/R
Mast (full load)	270 mm

### Engine Model

Engine Model	Isuzu 4JG2
Rated output	46/2450 kw/rpm
Rated torque	186/1600 Nm/rpm
No. Cylinder	4
Displacement cc	2369 cc
Transmission type	Hydraulic
Operating pressure	17.5 Mpa
Start Battery	12/80 V/Ah



Sales

022 6188 456

ph 0800 LANDEX (0800 526 339)

Address: 9-13 Sims Rd, Penrose



e-mail: sales@landex.co.nz

Postal: PO Box 58413, Botany, Manukau 2163

Parts and Service

0220 693 571

Website: www.landex.co.nz